







Standard trim

	EO	NL	NL-OP
			
<b>Product description</b>	22EO-F	22NL-F	22NL-OP-F
<b>Trim description</b>	—	210NL**	110NL-MD** 110NL-WD**
<b>Escutcheon plate size</b>	—	5 <sup>3</sup> / <sub>8</sub> " x 4 <sup>25</sup> / <sub>32</sub> " x 3 <sup>3</sup> / <sub>32</sub> " (137 x 121 x 2 mm)	—
<b>Pull center to center</b>	—	—	—
<b>Projection</b>	—	1 <sup>31</sup> / <sub>32</sub> " (42 mm)	—
<b>ANSI function</b>	01	03	03
<b>Cylinder type</b>	—	Rim	Rim
<b>Handing</b>	—	—	—
<b>Optional trim</b>	230EO	230NL	—
<b>Optional #425 sex bolt quantity for device</b>	6 (with no trim) 2 (with EO trim)	2	6
<b>*Additional 425 SNB for 499F strike</b>	2	2	2

\*Sex Bolts are required for wood fire doors

\*\*ANSI/BHMA A156.3 (2001) Grade 1 trim

	TP	K	L
			
<b>Product description</b>	22TP-F	22K-F	22L-F
<b>Trim description</b>	230TP**	210K	230L**
<b>Escutcheon plate size</b>	3" x 12 <sup>1</sup> / <sub>16</sub> " x 3 <sup>3</sup> / <sub>32</sub> " (76 x 306 x 2 mm)	3" x 4 <sup>25</sup> / <sub>32</sub> " x 3 <sup>3</sup> / <sub>32</sub> " (76 x 121 x 2 mm)	3" x 6 <sup>3</sup> / <sub>8</sub> " x 1 <sup>5</sup> / <sub>16</sub> " (76 x 162 x 24 mm)
<b>Pull center to center</b>	5 <sup>1</sup> / <sub>2</sub> " (140 mm)	—	—
<b>Projection</b>	2" (51 mm)	2 <sup>15</sup> / <sub>16</sub> " (75 mm)	2 <sup>5</sup> / <sub>8</sub> " (67 mm)
<b>ANSI function</b>	05	08	08
<b>Cylinder type</b>	1 <sup>1</sup> / <sub>4</sub> " Mortise	Furnished	1 <sup>1</sup> / <sub>4</sub> " Mortise
<b>Handing</b>	—	—	—
<b>*Optional trim</b>	230TP-BE	210K-BE	230L-BE
<b>Optional #425 sex bolt quantity for device</b>	2	2	2
<b>*Additional 425 SNB for 499F strike</b>	2	2	2

\*Sex Bolts are required for wood fire doors

\*\*ANSI/BHMA A156.3 (2001) Grade 1 trim