

22 Rim exit device



22 Rim exit device for all types of single and double doors with mullion, UL listed for Panic Exit Hardware. Devices are ANSI A156.3, 2001 Grade 1. Covers stock hollow metal doors with 161* cutouts. Fits door stiles as narrow as 3¹³/₁₆" (97 mm). The device is non-handed.

Finishes – SP28 & SP313.

*Not applicable with all strike and mullion combinations, consult factory.



The 299 Strike ships standard, optional strikes available

Hex key **dogging** comes standard on 22 Rim exit device



Specifications	
Device functions	Ships ready for all functions, EO, DT, NL, TP, K, L
Device lengths	3' (914 mm) see minimum door opening chart at bottom of page 4' (1219 mm) see minimum door opening chart at bottom of page
Device centerline from finished floor	39 ¹³ / ₁₆ " (1011 mm) 39 ¹¹ / ₁₆ " (1008 mm) with mullion
Center case dimensions	4 ¹ / ₄ " (108 mm) x 1 ³ / ₈ " (41 mm) x 2 ³ / ₈ " (60 mm)
Mechanism case dimensions	2" (51 mm) x 3 ³ / ₄ " (95 mm)
Projection push bar	Push bar neutral - 3 ³ / ₄ " (95 mm) push bar depressed - 3" (76 mm)
Latch bolt	Deadlocking, 3/4" (19 mm) throw
Fasteners & sex bolts (SNB)	Includes 1 ³ / ₄ " (44 mm) and 2 ¹ / ₄ " (57 mm) wood & metal doors optional SNB available for device
Electric options	LX latchbolt monitor switch RX pushpad monitor switch RX2 double pushpad monitor switch ALK alarm exit kit CON Allegion Connect
Mechanical options	GBK glass bead kit AX accessible device
Dogging feature	Hex key dogging standard
Dogging options	LD less dogging
Strikes	299 – Dull black

AX

Accessible device

- UL certified to meet new 5 lb. maximum operating force requirement
- Exceeds ANSI/BHMA requirements

RX

Pushpad monitor switch

- Signals use of an opening
- SPDT switch to monitor pushpad

RX2

Double pushpad monitor switch

- Uses two RX switches

ALK

Alarm exit kit

- Unauthorized opening triggers 85-decibel horn
- Set in armed or disarmed mode by key

LX

Latchbolt monitor switch

- Signals use of opening
- SPDT Switch to monitor latchbolt

CON

Allegion Connectors

- Common connectors to connect various door hardware all the way to the power supply

Minimum door opening chart

Stop height	Strike	Single door	Double door w/mullion	Minimum door opening for 3' device*	Minimum door opening w/ALK*
1/2"	299	Yes	—	26.500" (673mm)	33.250" (845mm)
1/2"	1439	Yes	—	25.687" (652mm)	32.437" (824mm)
1/2"	299	—	4754/4854/4954	27.000" (686mm)	33.750" (857mm)
1/2"	299	—	5654	25.812" (656mm)	32.562" (827mm)
1/2"	1408	—	5754	25.750" (679mm)	32.500" (826mm)
1/2"	1606	—	1654	26.562" (675mm)	33.312" (846mm)
5/8"	299	Yes	—	26.750" (679mm)	33.500" (851mm)
5/8"	1439	Yes	—	25.937" (659mm)	32.687" (830mm)
5/8"	299	—	4754/4854/4954	27.125" (689mm)	33.875" (860mm)
5/8"	299	—	5654	26.687" (678mm)	33.437" (849mm)
5/8"	1408	—	5754	25.875" (657mm)	32.625" (829mm)
5/8"	1606	—	1654	26.687" (678mm)	33.437" (849mm)

*For 4' device, add 6" (152mm)