

19-R SERIES NON-HANDED RIM DEVICE

Panic Exit Hardware

The Falcon 19-R Series rim device that delivers superior panic hardware with modern touchbar styling. This non-handed device covers a 161 cutout and may be used on 1³/₄" narrow stile aluminum doors. The "EO" (Exit Only) device is ready to accept any trim function shown on page 17.



DEVICE & TRIM	ANSI Type	ANSI Function
19-R-EO	1 or 4	01
19-R-DT	1 or 4	02
19-R-NL	1 or 4	03
19-R-K (or L or KIL)	1 or 4	08
19-R-K-NL (or L-NL or kil-nl)	1 or 4	09
19-R-TP-BE	1 or 4	
19-R-K-BE	1 or 4	
19-R-K-DT	1 or 4	
19-R-L-BE	1 or 4	
19-R-L-DT	1 or 4	
19-R-KIL-BE	1 or 4	
19-R-KIL-DT	1 or 4	

Note: For blank escutcheon specify BE.

Specifications

Hand:	Non-Handed.
Functions:	See trim selection chart on this page.
Finishes:	SP28, SP313, US32D. Centercase and end cap are powder-coated black only.
Strikes:	Standard - F570. Optional - F490, 565, 571, 571A.
Latch:	Stainless Steel, ³ / ₄ " throw dead locking.
Dogging Feature:	Hex key dogging standard. Cylinder dogging or less dogging optional.
Sizes:	3' for doors from 2'5" up to 3'. 4' for doors from 3' up to 4'.
Doors:	1 ³ / ₄ " thick metal or wood doors, specify if other.
Projections:	2 ¹ / ₂ " in neutral position, 1 ⁷ / ₈ " in dogged position. Pushbar height is 1 ³ / ₄ ".
Stile:	1 ³ / ₄ " minimum.
Fasteners:	All machine screw mounting. Device mounting fasteners are concealed, latch fasteners are exposed to egress side.
End Caps:	Black plastic end caps.
ANSI:	Certified ANSI A156.3 Grade 1 standards.